

# Versions

In this section, user can defines the versions of the selected project. Other than the basic CRUD operations, the following operations are also possible:

- Make Replica
  - To make a replica of version's test cases and API mocks, follow the steps below:
    - First select a version, for which you want to make a replica.
    - then click on "Make Replica" button to make a copy of the selected version. All the test cases and API mocks assigned to the selected versions are replicated and assigned to new version.
- Commit/Un-Commit
  - To commit/un-commit a version or a set of version, follow the steps below:
    - First select a version or a set of versions, which you want to commit/un-commit.
    - then click on "Commit"/"Un-Commit" button to perform the operation. All the test cases and API mocks assigned to selected version(s) are committed/un-committed.

The screenshot displays a web interface for managing versions. At the top left, the word "Versions" is written in a bold, sans-serif font. Below this, there is a horizontal row of five buttons: "New", "Delete", "Make Replica", "Commit", and "Un-Commit". Below the buttons is a table with two columns: "Name" and "Description". The table contains three rows of data, each with a checkbox in the "Name" column. The first row has "v1.0.0" in the "Name" column and "Initial Version" in the "Description" column. The second row has "v1.1.0" in the "Name" column and is empty in the "Description" column. The third row has "v1.3.0" in the "Name" column and is empty in the "Description" column.

<input type="checkbox"/> Name	Description
<input type="checkbox"/> v1.0.0	Initial Version
<input type="checkbox"/> v1.1.0	
<input type="checkbox"/> v1.3.0	